

PATENT
512425-2101

STATUS OF THE CLAIMS

Claim 1 (previously presented)

1. A cleaning and polishing oil-in-water emulsion which comprises:
 - A. about 0.1 to about 25 % of at least one silicone oil with a viscosity ranging between about 20 and about 100,000 mPas.;
 - B. about 0.5 to about 25 % of at least one bisquaternary organomodified silicone of the formula:

$$[Z-M-(R'R'')SiO-[(R'R'')SiO]_n-Si(R'R'')-M-Z]^{2+} 2 X^- \quad (I)$$
 whereby

Z is a quaternary nitrogen radical,

R' and R'' are independently from each other an alkyl or an aryl radical,

M is a divalent hydrocarbon radical having at least 4 carbon atoms which optionally contain at least one hydroxyl group and which may be interrupted by one or more oxygen atoms and/or groups of the type $-C(O)-$, $-C(O)O-$ or $-C(O)N-$,

n is a number between 1 and 200,

X⁻ is an inorganic or organic anion;
 - C. about 0.1 to about 15.0 % of at least one nonionic or amphoteric surfactant which has an alkyl chain length between 6 and 14 carbon atoms;
 - D. about 1 to about 40 % of at least one oil selected from the group of mineral oils, paraffin oils, petroleum distillates, hydrocarbon solvents, ester oils, triglycerides and cyclic silicone oils;
 - E. about 0.1 to about 15 % of at least one emulsifier;
 - F. about 20 to about 99 % water; and

optionally one or more auxiliaries selected from the group consisting of consistency enhancers, thickeners, stabilizers, fragrances, preservatives, antioxidants, dyes, abrasives, glycol ethers, alcohols, and builders.


Claim 2 (previously presented)

PATENT
512425-2101

2. The cleaning and polishing oil-in-water emulsion according to claim 1, wherein R' and R'' are independently a C₁-C₄ alkyl radical or a C₁₁-C₁₈ alkyl radical.

Claim 3 (previously presented)

3. The cleaning and polishing oil-in-water emulsion according to claim 1, wherein the bisquaternary organomodified silicone is a compound of the formula:



wherein

Z is the radical $-(R^1R^2R^3)N^+$ or $-(R^4R^5)N^+-(CH_2)_x-R^6-C(O)R^7$,

R¹, R², R³ independently from each other are C₁-C₂₂

R⁴, R⁵, and alkyl or C₂-C₂₂ alkenyl radicals optionally substituted by

R⁷ one more OH groups or a -CH₂-aryl radical,

x is number between 2 and 6,

R⁶ is an oxygen atom or a group -N(R⁸), wherein R⁸ is hydrogen, a C₁-C₄ alkyl or hydroxyalkyl radical,

M is a divalent hydrocarbon radical with at least 4 carbon atoms, which is optionally substituted with at least one hydroxyl group and which may be interrupted by one or more oxygen atoms and/or at least one radical selected from the group consisting of -C(O)-, -C(O)O- and -C(O)N-,

n is a number between 8 and 200, and

X⁻ is an inorganic or organic anion.

Claim 4 (previously presented)

4. The cleaning and polishing oil-in-water emulsion according to claim 1, wherein at least one of the variables of the R¹, R² or R³ is an alkyl radical having at least 10 carbon atoms or a benzyl radical.

PATENT
512425-2101

Claim 5 (previously presented)

5. The cleaning and polishing oil-in-water emulsion according to claim 1, wherein the bisquaternary organomodified silicone is a compound of the formula:



wherein

- Z is the radical $-(CH_3)_2N^+- (CH_2)_x-R^6-C(O)R^7$,
 R^7 is a C_{16} - C_{22} alkyl radical or a C_{16} - C_{22} alkylene radical, each of which is optionally substituted with one or more hydroxyl groups,
 x is number between 2 and 6,
 R^6 is an oxygen atom or a group $-N(R^8)$, wherein
 R^8 is hydrogen, a C_1 - C_4 alkyl radical or a C_1 - C_4 hydroxyalkyl radical,
 M is a divalent hydrocarbon radical with at least 4 carbon atoms, which optionally contain at least one hydroxyl group and which is optionally interrupted by one or more oxygen atoms and/or at least one radical selected from the group consisting of $-C(O)-$, $-C(O)O-$ and $-C(O)N-$,
 n is a number between 8 and 100, and
 X^- is an inorganic or organic anion.

Claim 6 (previously presented)

6. The cleaning and polishing emulsion according to claim 5, wherein X^- is an acetate ion.

Claim 7 (previously presented)

7. The cleaning and polishing oil-in-water emulsion according to claim 1, which comprises
- about 0.5 to about 10 % of at least one silicone oil with a viscosity ranging between about 50 and 50,000 mPas.;
 - about 0.5 to about 10 % of at least one bisquaternary organomodified silicone;
 - about 0.5 to about 10 % of at least one nonionic or amphoteric surfactants having an alkyl chain length between 8 and 12 carbon atoms;
 - about 5 to about 20 % of at least one oil selected from the group consisting of mineral oil, a hydrocarbon solvent, an ester oil, and a cyclopentasiloxane;
 - about 0.5 to about 10 % of an emulsifier which is a nonionic surfactants; and

PATENT
512425-2101

- F. about 60% to about 90% water.

Claim 8 (previously presented)

8. The cleaning and polishing oil-in-water emulsion according to claim 1, wherein
- A. about 1 to about 5 % of at least one silicone oil with a viscosity ranging between about 100 and 20,000 mPas.;
 - B. about 1% to about 5 % of at least one bisquaternary organomodified silicone;
 - C. about 2% to about 8% of at least one surfactant, wherein the surfactant is selected from the group consisting of ethylhexyl (poly)glucoside, capryl/caprylyl (poly)glucoside, decamine oxide, capryl/capramidopropyl betaine, undecylenamidopropyl betaine and sodium caprylamphopropionate;
 - D. about 5% to about 15% of at least one oil which is selected from the group consisting of a mineral oil, a hydrocarbon solvent, an ester oil, and a cyclopentasiloxane;
 - E. about 1% to about 7% of a nonionic emulsifier; and
 - F. about 70% to about 90% water.

Claim 9 (previously presented)

9. A cleaning and polishing oil-in-water emulsion according to claim 1, wherein
- A. about 1% to about 5% of at least one silicone oil with a viscosity ranging between about 100 and 20,000 mPas;
 - B. about 1% to about 5 % of at least one bisquaternary organomodified siloxanes;
 - C. about 2% to about 4% of at least one surfactant selected from the group consisting of ethylhexyl(poly)glucoside, capryl/caprylyl (poly)glucoside, and decamine oxide;
 - D. about 5% to about 15% of at least one oil which is selected from the group consisting of a mineral oil, a hydrocarbon solvent, cyclopentasiloxane and a mixture of the foregoing;
 - E. about 1 to about 5% of an emulsifier selected form the group consisting of sorbitan esters, ethoxylated sorbitan esters and a mixture of the foregoing; and

PATENT
512425-2101

F. about 75% to 90% water.

Claim 10 (previously presented)

10. A method for the preparation of a cleaning and polishing oil-in-water emulsion according to claim 1, which comprises:
1. producing an emulsion by homogenizing a mixture of components A, B, D and E with component F, and
 2. adding component C to the emulsion obtained above, optionally with a part of water of F and/or with a preservative and/or other auxiliaries.

Claim 11 (previously presented)

11. A pump dispenser which includes a cleaning and polishing emulsion according to claim 1.

Claim 12 (previously presented)

12. The pump dispenser according to claim 11, which is a non-pressurized foam pump dispenser.

Claim 13 (previously presented)

13. A method for cleaning and polishing a surface which comprises applying a portion of foam from the dispenser according to claim 11 and wiping the surface with a cloth or towel.

Claim 14 (previously presented)

14. A polish which comprise the oil-in-water emulsion according to claim 1.

Claim 15 (previously presented)

15. The polish according to claim 14, which is a furniture/wood polish or a car paint polish.

Claim 16 (previously presented)

16. The polish according to claim 14, which is a stainless steel polish or a plastic polish.

PATENT
512425-2101

Claim 17 (previously presented)

17. The polish according to claim 14, which is a leather polish.